

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PVC PRIME
Product code : 253-2-PRIME

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only/Industrial
Use of the substance/mixture : Primer

1.2.2. Uses advised against

The product is not recommended for any industrial, professional or consumer use other than the identified uses above.

1.3. Details of the supplier of the safety data sheet

POLYBIT WATERPROOFING SYSTEMS
3A Bellfrog Street, Greenacre NSW 2190
Sydney, Australia
T 02 9131 6224

1.4. Emergency telephone number

T +61 414 923 809

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Specific target organ toxicity — Repeated exposure, Category 2 H373
Aspiration hazard, Category 1 H304
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]



Hazard pictograms (CLP) :
Signal word (CLP) : Danger
Contains : butanone; ethyl methyl ketone; Reaction mass of ethylbenzene and m-xylene and p-xylene
Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.

Precautionary statements (CLP)

- H315 - Causes skin irritation.
- H319 - Causes serious eye irritation.
- H335 - May cause respiratory irritation.
- H336 - May cause drowsiness or dizziness.
- H373 - May cause damage to organs through prolonged or repeated exposure.
- : P260 - Do not breathe vapours.
- P280 - Wear protective gloves, face protection, eye protection.
- P302+P352 - IF ON SKIN: Wash with plenty of water.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER.
- P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.
- P501 - Dispose of contents to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butanone; ethyl methyl ketone substance with a Community workplace exposure limit	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3 (REACH-no) 01-2119457290-43	45 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Reaction mass of ethylbenzene and m-xylene and p- xylene substance with a Community workplace exposure limit	(EC-No.) 905-562-9 (REACH-no) 01-2119488216-32	45 – 50	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304

Comments

- : If REACH registration numbers do not appear, the substance is either exempt from registration or does not meet the minimum volume threshold for registration.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. Wash with plenty of water/... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs.
Symptoms/effects after inhalation	: May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedure

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing vapours.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Use only non-sparking tools. Avoid breathing vapours. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids..
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butanone; ethyl methyl ketone (78-93-3)

EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	600 mg/m ³
IOEL TWA [ppm]	200 ppm
IOEL STEL	900 mg/m ³
IOEL STEL [ppm]	300 ppm

Reaction mass of ethylbenzene and m-xylene and p-xylene

EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	221 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

butanone; ethyl methyl ketone (78-93-3)

DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation	1161 mg/kg bodyweight/day 600 mg/m ³
DNEL/DMEL (General population) Long-term - systemic effects, oral Long-term - systemic effects, inhalation Long-term - systemic effects, dermal	31 mg/kg bodyweight/day 106 mg/m ³ 412 mg/kg bodyweight/day
PNEC (Water) PNEC aqua (freshwater) PNEC aqua (marine water) PNEC aqua (intermittent, freshwater)	55,8 mg/l 55,8 mg/l 55,8 mg/l
PNEC (Sediment) PNEC sediment (freshwater) PNEC sediment (marine water)	284,74 mg/kg dwt 284,7 mg/kg dwt
PNEC (STP) PNEC sewage treatment plant	709 mg/l

Reaction mass of ethylbenzene and m-xylene and p-xylene

DNEL/DMEL (Workers) Acute - systemic effects, inhalation Acute - local effects, inhalation Long-term - systemic effects, dermal Long-term - systemic effects, inhalation Long-term - local effects, inhalation	442 mg/m ³ 442 mg/m ³ 212 mg/kg bodyweight/day 221 mg/m ³ 221 mg/m ³
DNEL/DMEL (General population) Acute - systemic effects, inhalation Acute - local effects, inhalation Long-term - systemic effects, oral	260 mg/m ³ 260 mg/m ³ 12,5 mg/kg bodyweight/day

Long-term - systemic effects, inhalation	221 mg/m ³
Long-term - local effects, inhalation	221 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	260 mg/m ³
Acute - local effects, inhalation	260 mg/m ³
Long-term - systemic effects, oral	12,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	65,3 mg/m ³
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65,3 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	327 µg/L
PNEC aqua (marine water)	327 µg/L
PNEC aqua (intermittent, freshwater)	327 µg/L
PNEC (Sediment)	
PNEC sediment (freshwater)	12,46 mg/kg dwt
PNEC sediment (marine water)	12,46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2,31 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	6,58 mg/l

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment

: Avoid all unnecessary exposure.



Personal protective equipment symbols

8.2.2.1. Eye and face protection

Eye protection

: Safety glasses with side shields. Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection

: Wear suitable protective clothing. Personal protective equipment for the body and appropriate footwear should be selected depending on the task being performed and possible exposure

Hand protection

: Suitable materials for safety gloves (EN 374):
Butyl rubber, Nitrile rubber, neoprene rubber. For prolonged or repeated exposure, gloves of class 5 or higher are recommended (breakthrough time → 240min according to EN374). For short time use, gloves of class 3 or higher are recommended (breakthrough time → 60min according to EN374). The thickness of gloves should be → 0.35mm in order to provide adequate protection for prolonged contact with the product. Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection

: If concentration of one or more substances present in the product exceeds the exposure limit, use respiratory protective device (refer to EN 529). Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. [In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls

: Avoid release to the environment.

Other information

: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Transparent.
Odour	: characteristic.
Odour threshold	: No data available
pH	: Not applicable, product is solvent-based
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: → 80 °C
Flash point	: -4 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly Flammable liquid and vapour.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,8 – 0,9 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: ← 20,5 mm ² /s
Viscosity, dynamic	: No data available
Explosive properties	: Not applicable, product is not explosive
Oxidising properties	: Not applicable, product is not oxidising
Explosive limits	: No data available

9.2. Other information

VOC content	: 808 g/l
-------------	-----------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Sparks. Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Reaction mass of ethylbenzene and m-xylene and p-xylene

LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	12126 mg/kg
LC50 Inhalation - Rat (Vapours)	27124 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable, product is solvent-based
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable, product is solvent-based
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: May cause respiratory irritation. May cause drowsiness or dizziness.

butanone; ethyl methyl ketone (78-93-3) STOT-single exposure Reaction mass of ethylbenzene and m-xylene and p-xylene STOT-single exposure	May cause drowsiness or dizziness May cause respiratory irritation.
--	--

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Reaction mass of ethylbenzene and m-xylene and p-xylene STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
--	--

Aspiration hazard : May be fatal if swallowed and enters airways.

PVC PRIME	
Viscosity, kinematic	→ 20,5 mm ² /s

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

butanone; ethyl methyl ketone (78-93-3) LC50 - Fish [1] Reaction mass of ethylbenzene and m-xylene and p-xylene LC50 - Fish [1] NOEC chronic fish	2,993 g/l LC50 96h fish 2,6 mg/l LC50 96h fish 1,3 mg/l
---	---

12.2. Persistence and degradability

PVC PRIME	
Persistence and degradability	No available data.

12.3. Bioaccumulative potential

TPO PRIME	
Bioaccumulative potential	No available data.

Reaction mass of ethylbenzene and m-xylene and p-xylene	
Bioconcentration factor (BCF REACH)	25,9

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to a hazardous or special waste collection point.

Additional information

: Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials

: Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : UN 1993
UN-No. (IMDG) : UN 1993
UN-No. (IATA) : UN 1993
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, N.O.S
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S
Proper Shipping Name (IATA) : FLAMMABLE LIQUID, N.O.S
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable
Transport document description (ADR) : UN 1993 FLAMMABLE LIQUID, N.O.S. (contains xylene and toluene), 3, II, (D/E)
Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S. (contains xylene and toluene), 3, II
Transport document description (IATA) : UN 1993 Flammable liquid, n.o.s., 3, II

14.3. Transport hazard class(es)

ADR
Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3





IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : II
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 274, 601, 640D
Limited quantities (ADR) : 1L
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Mixed packing provisions (ADR) : MP19
Special provisions for carriage -
Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3YE

Transport by sea

Special provisions (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : B

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 3H

Inland waterway transport

No data available

Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 808 g/l

15.1.2. National regulations

France

Occupational diseases

Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
Persons suffering from asthma or eczema and persons who have chronic lung diseases, skin or respiratory allergies to isocyanates should not work with the material
The requirements from the Danish Working Environment Authorities regarding work with epoxy resins and isocyanates must be observed during use and disposal
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Switzerland

Storage class (LK) : LK 3 - Flammable liquids

15.2. Chemical safety assessment

No data available

SECTION 16: Other information

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.